

**SAV 240.41****HOLDING MAGNETS WITH RUBBER COATING**

With threaded bush

**DESIGN**

Rubber-coated holding magnets, disc-shaped. Rectangular version with 1 or 2 threaded bushes. The Santoprene® rubber coating has a very long useful life and is sufficiently resistant to all weather conditions and UV radiation.

Max. service temperature: 60 °C.

**APPLICATION**

The rubber-coated holding magnets are ideal for attaching items such as advertising displays, safety lamps on car roofs, but also

for scratch-free attaching of signs or sample parts to mirror-polished, chrome-plated or painted steel surfaces.

**MAGNET MATERIAL**


NdFeB

**FASTENING OPTION**

Screws



Type	mm					Rated holding force	kg
	A	B	C	D	E		
MG 12	12	7	14.8	8	M 4	10	0.006
MG 22	22	6	11.5	8	M 4	50	0.013
MG 31	31	6	11.5	8	M 4	75	0.022
MG 43	43	6	10.5	8	M 4	85	0.030
MG 66	66	8.5	15	10	M 5	180	0.105
MG 88	88	8.5	17	12	M 8	420	0.192

**ORDERING EXAMPLE**

Designation	SAV no. - type
Holding magnet	SAV 240.41 - MG 12