

SAV 240.02

HOLDING MAGNETS

Stud with internal thread (flat pot magnet)

DESIGN

Flat pot magnet with threaded bush.
 Shielded system, galvanised surface.
 Version (RF) available for sizes with stated holding force. Max. service temperature: 200 °C.

MAGNET MATERIAL


Hard ferrite (oxide 380)

FASTENING OPTION

Screws



Type	mm						Rated holding force N	Weight kg	RF Rated holding force N	RF C
	A ±0.2	B ±0.2	C	D ±0.2	E ±0.2	F ±0.2				
MH 2 - 01	10	4.5	M 3	6	11.5	7	4	0.003	-	-
MH 2 - 02	13	4.5	M 3	6	11.5	7	10	0.004	-	-
MH 2 - 03	16	4.5	M 3	6	11.5	7	18	0.006	-	-
MH 2 - 04	20	6	M 3	6	13	7	30	0.011	-	-
MH 2 - 05	25	7	M 4	8	15	8	40	0.020	32	M 5
MH 2 - 06	32	7	M 4	8	15	8	80	0.031	64	M 5
MH 2 - 36	36	7.7	M 4	8	16	8	100	0.042	-	-
MH 2 - 07	40	8	M 5	10	18	10	125	0.059	100	M 5
MH 2 - 47	47	9	M 6	12	21	12	180	0.091	-	-
MH 2 - 08	50	10	M 6	12	22	12	220	0.110	175	M 5
MH 2 - 57	57	10.5	M 6	12	22.5	12	280	0.153	-	-
MH 2 - 09	63	14	M 8	15	30	16	350	0.245	280	M 5
MH 2 - 10	80	18	M 10	20	34	16	600	0.499	-	-
MH 2 - 11	100	22	M 12	22	43	21	900	0.956	-	-
MH 2 - 12	125	26	M 14	25	50	20	1300	1.720	-	-



ORDERING EXAMPLE

Designation	SAV no. - type - stainless version
Holding magnet	SAV 240.02 - MH 2 - 12 - RF