

SAV 240.71

MAGNETIC TAPES

Can be cut with scissors, adhesive on one side

DESIGN

Polymer-bonded magnet, can be cut with scissors.

FASTENING OPTION

Magnetic tapes. Type MB 51 with almost non-magnetic rear side and self-adhesive coating.

Permaflex 424 holding force:
 Thickness 1.0 mm: 0.55 N/cm²
 Thickness 1.5 mm: 0.57 N/cm²
 Thickness 2.0 mm: 0.58 N/cm²



Magnetic tape, coloured MB 50:
 black (SW), white (WS), red (RT), blue (BL), green (GR), yellow (GB)

Type	mm		m
	Width	Thick-ness	
MB 50 - 10	10	0.8	10
MB 50 - 15	15	0.8	10
MB 50 - 20	20	0.8	10
MB 50 - 25	25	0.8	10
MB 50 - 30	30	0.8	10
MB 50 - 35	35	0.8	10
MB 50 - 40	40	0.8	10
MB 50 - 50	50	0.8	10
MB 50 - 60	60	0.8	10
MB 50 - 70	70	0.8	10
MB 50 - 80	80	0.8	10
MB 50 - 90	90	0.8	10
MB 50 - 100	100	0.8	10

ORDERING EXAMPLE

Designation	SAV no. - type - colour
Magnetic tape	SAV 240.71 - MB 50 - 10 - SW

SAV 240.71

MAGNETIC TAPES

Can be cut with scissors, adhesive on one side

DESIGN

Polymer-bonded magnet, can be cut with scissors.

FASTENING OPTION

Magnetic tapes. Type MB 51 with almost non-magnetic rear side and self-adhesive coating.

Permaflex 424 holding force:
 Thickness 1.0 mm: 0.55 N/cm²
 Thickness 1.5 mm: 0.57 N/cm²
 Thickness 2.0 mm: 0.58 N/cm²



Magnetic tape, C-profile MB 54:
 Flexible magnetic label strips

Type	mm		m
	Width	Length per roll	
MB 54 - 10	10	50	
MB 54 - 15	15	50	
MB 54 - 20	20	50	
MB 54 - 25	25	50	
MB 54 - 30	30	50	
MB 54 - 40	40	50	
MB 54 - 50	50	50	